



STANDARD DUTY
REAR-MOUNT

FINISH MOWERS

FEATURES

Deep 4.6-inch deck, baffling and unique rear discharge design ensures exceptional material distribution

Spring-loaded idler arms automatically maintain the correct tension on our custom-made belts

Tubular caster arms and heavy, tall deck rail supports (4.5-inches) for increased strength and durability

Turn acres of grass into well-groomed acres of lawn.

There's nothing more rewarding than a lawn that's finely groomed like a country club fairway. Especially when it doesn't take all day to make it look that way. That's why our finish mowers are engineered for speed, precision and enduring quality. The innovative rounded-front, tapered-side, rear-discharge deck allows you to reduce trim and mow with better maneuverability. And the heat-treated, alloy steel blades always give you a beautiful, high-precision cut on any type of grass.

YFM54 shown with optional chain shielding*

*All YFM Series finish mower models pass all applicable safety standards for thrown object and blade contact without chain shielding. However, if these units will be used in areas where the possibility of thrown objects could be hazardous to persons or property, it is strongly recommended that optional chain shielding be used for extra protection.

INNOVATIVE DESIGN AND TECHNOLOGY



ROUNDED FRONT CORNERS

and tapered deck sides improve maneuverability and grass discharge.



BOX-STYLE CONSTRUCTION

for superior deck strength.



STANDARD DUTY

MODEL	YFM60B	YFM627B	YFM72
Tractor PTO HP Range	15-25	20-35	
Hitch/Quick Hitch Compatible	Cat 1/Yes		
Cutting Width (in.)	60	72	
Weight (lbs)	503	603	
Cutting Height Range (in.)	1-5.5		
Overall Width (in.)	661	73	73
Deck Material Thickness	10-gauge		
Side Skirt (in.)	7-gauge x 4.8 deep		8-gauge x 4.6 deep
Gearbox HP Rating	35		
Blade Tip Speed (FPM)	17,900	18,000	
Blade Spindles/Bearings	3 cast iron housings/greasable ball bearings		
Tractor PTO Speed (RPM)	540		
Driveline Size	Cat 3		
Belt	B-Section Kevlar®		
Belt Adjustment	Spring-loaded idler		
Rear Chain Shielding	Optional		
Mower Warranty	1 year residential or 90 day commercial		
Gearbox Warranty (Limited)	3 year homeowners or 1 year commercial		
Wheels	solid rubber wheels		pneumatic rubber wheels or solid rubber wheels

Yanmar has a corporate policy of continuous product improvement and development; therefore, data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manuals. Before operating a machine, read, understand, and follow all instructions in the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.