

STANDARD AND
MEDIUM DUTY

REAR BLADES



Scrape, grade and level almost any playing field.

A good rear blade is like a trusty pocketknife. You never run out of uses for it. Whether you're landscaping the yard, grading driveways or field roads, cleaning up a construction site, plowing snow or even cleaning livestock pens, you can always count on the strength and durability of these blades. Quickly and easily adjust the tilt, angle and offset to make short work of any job.

INNOVATIVE DESIGN AND TECHNOLOGY



ASABE QUICK HITCH COMPATIBILITY

for faster, easier and safer hook-ups.



REVERSIBLE/REPLACEABLE HIGH-CARBON CUTTING EDGE

FEATURES

Formed, curved moldboards for exceptional rigidity and strength (Standard Duty models)

360-degree pivoting blade with forward/reverse positions

Convenient parking stand standard

Five forward and five backfill angles, plus six offset positions (Medium Duty models)



STANDARD DUTY

MODEL	YRB54S	YRB60S	YRB72S
Tractor Engine HP Range	up to 30 hp	up to 30 hp	
Tractor Hitch	Limited Cat 1 and 1		
Working Width (in.)	54	60	72
Approximate Weight (lbs)	134	142	156
Moldboard Height (in.)	12		
Moldboard Thickness (in.)	3/16 (grade 80 steel)		
Reversible Cutting Edge	3/8" x 6"		
Pivot Angle	Forward - 5 @ 15 degrees, Reverse - 5 @ 15 degrees		
Skid Shoes	Optional		
ASABE Quick Hitch Compatible	Yes		
Parking Stand	Optional		

STANDARD DUTY (PREMIUM)

MODEL	YRB60C	YRB72C	YRB84C
Tractor Engine HP Range	20-45 hp		
Tractor Hitch	Cat 1		
Working Width (in.)	60	72	84
Approximate Weight (lbs)	268	288	308
Moldboard Height (in.)	15		
Moldboard Thickness (in.)	1/4 (grade 80 steel)		
Reversible Cutting Edge	1/2" x 6"		
Pivot Angle	Forward - 5 @ 15 degrees, Reverse - 5 @ 15 degrees		
Tilt	up to 15 degrees		
Offset	up to 12" left or right		
End Plates	Optional		
Skid Shoes	Optional		
ASABE Quick Hitch Compatible	Yes		
Parking Stand	Optional		

Yanmar has a corporate policy of continuous product improvement and development; therefore, data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manuals. Before operating a machine, read, understand, and follow all instructions in the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.